



# Green Laser measurer




Green Laser



NI-MH Rechargeable  
Battery



Digital Angle



2.0 inch Screen



Protection Class

Model	S8G	Add/Subtract	√
Range ( M)	0.2-40/60/80/100	Angle display	√
Accuracy(MM)	±(2mm+5×10-5Dmm)	Reference	Front/Tripod/Rear
Single Mea	√	Units	m/ft/in/ft+in
Continuous Mea	√	Auto shutoff	180s after inactivity
Area	√	Screen	2.0 inch reverse display
Volume	√	Protection class	IP65
Pythagoras (2- points)	√	Laser class	Class 2
Pythagoras (3- points) ①	√	Laser type	Green laser, 505-515nm, <1mW
Pythagoras (3- points) ②	√	Battery type	3xAAA NI-MH rechargeable batteries
Auto level	√	Operating temperature	0℃~+40℃ (32°F~+104°F)
Auto height	√	Size ( mm)	115*49*26

### 1.Measuring Range:

The Maximum range shall be different according to different models. The actual range refers to the package.

### 2. Measuring Accuracy:

If measuring under favorable conditions, such as smooth face, proper temperature and indoor lighting, the device is able to work within certain range as declared.Maximum deviation occurs under unfavorable conditions such as bright sunlight or when measuring to poorly reflecting or very rough surfaces

### Tips:

In case of bright sunlight and bad reflection of the object, please use the target plate or reflector.